



## Techniclean HP

High pressure spray process cleaner

### Description

Castrol Techniclean™ HP is an aqueous, low alkalinity, industrial cleaner containing biodegradable surfactants and corrosion inhibitors.

### Application

Techniclean HP is an inter-operational, multi-metal cleaner, suitable for cleaning parts and components in a wide range of industrial spray and intensive flood wash machines. Techniclean HP is specifically developed for use in high-pressure process cleaning and deburring equipment. Techniclean HP effectively removes soluble oils, light duty neat cutting or forming oils, lubrication oils, soft film corrosion preventives, swarf and general dirt.

### Conditions of Use

Optimum conditions of use are depending on the detailed application requirements and the amount and nature of the soil being removed.

### Advantages

- Effectively minimises excessive foam – reliable, reduces costly risk of dangerous cavitations/damage of high-pressure pumps
- Excellent demulsifying properties provide easy skimming and long bath life – reduces maintenance and disposal cost
- Leaves a temporary corrosion preventive film on the metal surface – minimises scrap rate which improves productivity
- Versatile; multi-metal compatibility and suitable in hard and soft water – enables possible product consolidation

### Typical Characteristics

Name	Method	Units	

## Typical Physical Characteristics

	Test Method	Unit	Value
Appearance	Visual	-	Clear, light yell
Density @ 15°C	DIN 51 757	kg/m <sup>3</sup>	1040
Density @ 59°F	DIN 51 757	lb/gal	8.7
pH (5% in DI-water)		-	9.3

## Recommended Concentrations

Concentration Range.	1 - 4%
Temperature Range:	Ambient - 65°C / 150°F
Spray Pressure	up to 1000 bar / 14500 psi

Techniclean HP  
18 Sep 2017  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

199 Oxford Road, Dunkeld, Johannesburg, 2196, South Africa  
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)  
[www.castrol.co.za](http://www.castrol.co.za)